# Tersus TC50 Controller

#### **Overview**

The TC50 Controller is a rugged multifunctional data controller with design of 5 inch sunlight readable HD touch screen and an alphanumerical keypad. Equipped with powerful Octa-core processor and android operating system, it is perfect to adapt with Tersus survey software.

With professional IP68 rating, it is robust and reliable for outdoor harsh environment. The large capacity lithium battery guarantees more than 10 hours of field working for a whole day of multiple surveying tasks.

### **Key Features**

- ✓ 5 inch sunlight readable HD touch screen
- ✓ Octa-core 2.0GHz CPU
- ✓ Android 8.1 operating system
- ✓ 4GB RAM + 64GB ROM
- ✓ 5MP front camera and 13MP rear camera
- ✓ IP68 certified grade, water/shock/dust proof
- ✓ 7000mAh battery
- ✓ Wi-Fi, Bluetooth, NFC, 4G
- ✓ USB Type-C





## Technical Specifications

System	
Operating system	n: Android 8.1
CPU:	MT6763 Octa-core 2.0GHz
Memory:	4GB RAM + 64GB ROM
External storage:	Micro SD , up to 128GB
Display:	5" sunlight-readable
	capacitive touch screen
Resolution:	720x1280
Camera:	5MP front , 13MP rear
Flash light:	High light flash LED

Commun	ication		
Wi-Fi:	IEEE 802.11a/b/g/n 2.4G&5G		
Cellular mo	de: Dual SIM Dual Standby		
SIM slot:	2 Micro SIM slots		
SIM1 & SIM2:			
	FDD-LTE B1/B3/B5/B7/B8		
	TD-LTE B38/B39/B40/B41		
	TDSCDMA B34/B39		
	WCDMA B1/B2/B5/B8		
CDMA1x/CDMA2000 BC0/BC			
	GSM B2/B3/B5/B8		
Bluetooth:	BT4.1 (BLE)		
USB:	USB Type-C (supports OTG)		
NFC: Prot	tocol of ISO14443A/B, ISO15693		
	Readable distance 0~5cm		
GNSS:	GPS/GLONASS/BeiDou		
Sensors:			
G-Sensor, Compass, Light-Sensor, Gyro			

Electrical	
Battery:	7000mAh 3.8V
Battery life:	14 hours
Charging time:	<4 hours (fast charge)
Physical	
Dimension:	207mmx84mmx20mm
Weight:	370g (include battery)

Environmental			
Operating Temperature:		-20°C ~ +55°C	
Storage Temperature:		-30°C ~ +70°C	
Humidity:		5% ~ 95%	
Dust-proof & Waterproof:		IP68	
Shock:	1.5m drop onto concrete		

Website | www.tersus-gnss.com
Sales Inquiry | sales@tersus-gnss.com
Technical Support | support@tersus-gnss.com

